

4AA

XPP-5564RXA/GXA

INTRINSICALLY SAFE DUAL-LIGHT ANGLE LIGHT

NIGHTSTICK[®]
Life Depends on Light™

INTRANTDUO




Battery status indicator - green indicates full charge and glows red when battery is nearing low



275 lumen floodlight - wide illumination at precise 45° downward angle



Easy press switches, independently controlling separate LEDs



Spring loaded clip and V-ring **securely hold tight to gear** in any situation



AVAILABLE IN HI-VIZ GREEN.



320 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

INTRANT DUO

DUAL-LIGHT ANGLE LIGHT

4AA**ITEM NUMBER/UPC**

XPP-5564RXA (Red), 017398809245
 XPP-5564GXA (Green), 017398809238

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cETLus, ATEX, IECEx, NFPA

CASE MATERIAL

- PC/ABS

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 320L, 8 hrs. runtime
 - LOW: 100L, 15 hrs. runtime

FLOODLIGHT

- HIGH: 275L, 8 hrs. runtime
 - LOW: 100L, 28 hrs. runtime

DUAL-LIGHT

- 320L, 5 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 22,107
 - LOW: 7,333

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 297m
 - LOW: 171m

WATER RATING

- IP-67 (Dustproof and Waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
 - WIDTH: 2.75 in (70 mm)
 - DEPTH: 2.5 in (64 mm)
 - HEAD DIAMETER: 2.75 in (70 mm)
 - WEIGHT: 11 oz (312g with batteries)

BATTERY







- 4AA batteries (included)

WARRANTY

- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
 - 4AA batteries
 - Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	320 LUMENS	100 LUMENS	320 LUMENS
	8h	15h	5h
	300m		
	22107cd		
	2m		
	1m		

Bayco Products, Inc. XPP-5564GXA/RXA
 640 S. Sanden Blvd., Wylie, TX 75098



Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 For use with Bayco 5564-CARRIER with 4 AA Energizer Type
 EN91, E91, Panasonic LR6XWA or Duracell MN1500 batteries only

Intertek

ID 5012927
 ELECTRICAL SAFETY
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV1 GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia IIC T4 Ga
 ZONE 20 AEx ia IIC T135°C Da
 I I M1 Ex ia I Ma
 II 1 G Ex ia IIC T4 Ga
 II 1 D Ex ia IIC T135°C Da

Ex ia I Ma
 Ex ia IIC T4 Ga
 Ex ia IIC T135°C Da
 IECEx: IECEx ETL 23.0048X
 ATEX: ITS I24ATEX39286X
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell Alkaline

CE 2575



CERTIFIED

