

3 AAA (included)

XPP-5450G

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

# NIGHTSTICK®

Life Depends on Light™




Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**Single Body Switch.** High-brightness Spotlight, Low-brightness Spotlight



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



**Adjustable ratchet tilt head** made from an engineered polymer housing



**90 LUMENS**

1-800-233-2155 · 1-469-326-9400 · [nightstick.com](http://nightstick.com)

© 2024 BPI Items shown are intended as a visual representation only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

**3 AAA INCLUDED**

**ITEM NUMBER/UPC**

- XPP-5450G, UPC 0 1739880300 7

**MARKET APPLICATIONS**

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

**CERTIFICATIONS**

- cETLus, CE, ATEX, IECEx, Kosha, INMETRO

**CASE MATERIAL**

- Engineered Polymer

**SPOTLIGHT LUMENS/RUNTIME**

- HIGH: 90L, 13.5 hrs. runtime  
 - LOW: 50L, 22.75 hrs. runtime

**CANDELA**

- HIGH: 1,615  
 - LOW: 1,076

**BEAM DISTANCE**

- HIGH: 80m  
 - LOW: 65m

**DUST/WATER RATING**

ANSI IP-67 Dustproof / Waterproof

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 2.4 in (61 mm)  
 - WIDTH: 1.9 in (48 mm)  
 - DEPTH: 1.8 in (46 mm)  
 - WEIGHT: 3.5 oz (99 g)

**BATTERY**

- 3 AAA (Included)

**WARRANTY**

- Limited lifetime warranty

**WHAT'S INCLUDED**

- Headlamp  
 - 3 AAA batteries  
 - Elastic non-slip headband  
 - Rubber hardhat strap  
 - Instruction manual

FL 1 STANDARD	HIGH	LOW
	<b>90 LUMENS</b>	<b>50 LUMENS</b>
	<b>13h</b>	<b>22h</b>
	<b>80m</b>	<b>65m</b>
	<b>1615cd</b>	<b>1076cd</b>
	<b>2m</b>	
	<b>1m</b>	

**NIGHTSTICK** XPP-5450G

Bayco Products, Inc. 640 S. Sanden Blvd., Wylie, TX 75098

 Intertek ID 4003544 INTRINSICALLY SAFE SECURITE INTRINSEQUE	CE 2575 UK CA 0359  22-AV4B0-0216X	CLASS I DIV 1 GRPS A-D T4 CLASS II & III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T4 Ga CLASS I ZONE 0 Ex ia IIC T4 Ga Ex ia op is IIC T4 Ga Intertek ITS 13 ATEX27854X ITS21UKEX0247X IECEx ITS 17.0002X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAA Alkaline
--	---	--

SEE INSTRUCTION MANUAL  
VOIR MANUEL

MFG MM-YY



© 2024 BPI Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5450G-24

